

signDRIVE 4

Technical specifications

- Voltage: AC100~240V...50/60Hz
- Power Consumption: 200W
- Output Line: 4 Lines
- Output Current: 350mA per color
- Output per Line: 36 x 1W LED (12W per color)
- Total Output: 144 x 1W LED (48W per color)
- Control: DMX512
- Personalities: 6
- DMX Channels: 3CHS/ 4CHS/ 6CHS/ 9CHS/ 12CHS/ 15CHS
- Operation: DMX, Master/Slave, Stand-alone
- Functions: RGB calibration, RGB to White, Play schedule, Static
- Built-in Programs: 20
- Custom Programs: 10
- DMX Connection: RJ45
- Display: LCD
- Ambient Temperature: -20°C/+40°C
- Weight: 2Kg
- Dimensions: 320 x 230



signLINEA 12

Technical specifications

- Input Current: 350mA
- Power Consumption: 12.9W
- Light Source: 12 x 1W LED (RGB)
- Standard Optic: 25 x 6°
- Optional Optic: 12°/ 30°
- Compatible Driver: signDRIVE 4
- Ambient Temperature: -20°C/ +40°C
- Cooling System: convection
- Construction: extruded aluminium
- Weight: 0.76Kg
- Dimensions: 402 x 57 x 75 mm

- Installation: universal
- Ingress Protection: IP 2X
- Flammability: 94 V-0 flame class rating
- Power/ Data Connection: RJ45
- Power/ Data Cable: 26



signLINEA 24

Technical specifications

- Input Current: 350mA
- Power Consumption: 25.8W
- Light Source: 24 x 1W LED (RGB)
- Standard Optic: 25 x 6°
- Optional Optic: 12° / 30°
- Compatible Driver: signDRIVE 4
- Ambient Temperature: -20°C / +40°C
- Cooling System: convection
- Construction: extruded aluminium
- Weight: 1.35Kg
- Dimensions: 798 x 57 x 75 mm
- Installation: universal
- Ingress Protection: IP 2X
- Flammability: 94 V-0 flame class rating
- Power/ Data Connection: RJ45
- Power/ Data Cable: 26 AWG x 4P; cat.5e; 1.5m



signLINEA 12i

Technical specifications

- Input Current: 350mA
- Power Consumption: 12.8W
- Light Source: 12 x 1W LED (RGB)
- Standard Optic: 120°
- Compatible Driver: signDRIVE 4
- Ambient Temperature: -20°C/ +40°C
- Cooling System: convection
- Construction: extruded aluminium
- Weight: 0.67Kg
- Dimensions: 402 x 53 x 66 mm
- Installation: universal
- Ingress Protection: IP 2X
- Flammability: 94 V-0 flame class rating
- Power/ Data Connection: RJ45
- Power/ Data Cable: 26 AWG x 4P; cat.5e; 1.5m



signLINEA 24i

Technical specifications

- Input Current: 350mA
- Power Consumption: 25.6W

- Light Source: 24 x 1W LED (RGB)
- Standard Optic: 120°
- Compatible Driver: signDRIVE 4
- Ambient Temperature: -20°C/ +40°C
- Cooling System: convection
- Construction: extruded aluminium
- Weight: 1.67Kg
- Dimensions: 798 x 53 x 66 mm
- Installation: universal
- Ingress Protection: IP 2X
- Flammability: 94 V-0 flame class rating
- Power/ Data Connection: RJ45
- Power/ Data Cable: 26 AWG x 4P; cat.5e; 1.5m



signSOMA 3

Technical specifications

- Input Current: 350mA
- Power Consumption: 3.2W
- Light Source: 3 x 1W LED (RGB)
- Standard Optic: 30°
- Optional Optic: 12°
- Compatible Driver: signDRIVE 4
- Ambient Temperature: -20°C/ +40°C
- Cooling System: convection
- Construction: cast & extruded aluminium
- Weight: 0.17Kg
- Dimensions: 42 x Φ 49.8mm
- Installation: standard MR16 enclosure
- Ingress Protection: IP 2X
- Flammability: 94 V-0 flame class rating
- Power/ Data Connection: RJ45
- Power/ Data Cable: 26 AWG x 4P; cat.5e; 1.5m



signSOMA 3/1

Technical specifications

- Input Current: 350mA
- Power Consumption: 3.2W
- Light Source: 3W LED (tri-color)
- Standard Optic: 20°
- Compatible Driver: signDRIVE 4
- Ambient Temperature: -20°C/ +40°C
- Cooling System: convection
- Construction: cast & extruded aluminium
- Weight: 0.17Kg
- Dimensions: 48 x Ø49.8mm
- Installation: standard MR16 enclosure
- Ingress Protection: IP 2X
- Flammability: 94 V-0 flame class rating
- Power/ Data Connection: RJ45
- Power/ Data Cable: 26 AWG x 4P; cat.5e; 1.5m



signSOMA 6

Technical specifications

- Input Current: 350mA
- Power Consumption: 6.4W
- Light Source: 6 x 1W LED (RGB)
- Standard Optic: 30°
- Compatible Driver: signDRIVE 4
- Ambient Temperature: -20°C/ +40°C
- Cooling System: convection
- Construction: cast & extruded aluminium
- Weight: 0.2Kg
- Dimensions: 71.7 x Ø49.8mm
- Installation: standard MR16 enclosure
- Ingress Protection: IP 2X
- Flammability: 94 V-0 flame class rating
- Power/ Data Connection: RJ45
- Power/ Data Cable: 26 AWG x 4P; cat.5e; 1.5m



signSOMA 12

Technical specifications

- Input Current: 350mA
- Power Consumption: 12.9W
- Light Source: 12 x 1W LED (RGB)
- Standard Optic: 30°
- Optional Optic: 12°
- Compatible Driver: signDRIVE 4
- Ambient Temperature: -20°C/ +40°C
- Cooling System: convection
- Construction: cast & extruded aluminium
- Weight: 0.63Kg
- Dimensions: 43.5 x Ø110.8mm
- Installation: standard AR1-11 enclosure

- Ingress Protection: IP 2X
- Flammability: 94 V-0 flame class rating
- Power/ Data Connection: RJ45
- Power/ Data Cable: 26 AWG x 4P; cat.5e; 1.5m



signSOMA 12/4

Technical specifications

- Input Current: 350mA
- Power Consumption: 12.9W
- Light Source: 4 x 3W LED (tri-color)
- Standard Optic: 20°
- Compatible Driver: signDRIVE 4
- Ambient Temperature: -20°C/ +40°C
- Cooling System: convection
- Construction: cast & extruded aluminium
- Weight: 0.64Kg
- Dimensions: 49.4 x Φ 110.8mm
- Installation: standard AR1-11 enclosure
- Ingress Protection: IP 2X
- Flammability: 94 V-0 flame class rating
- Power/ Data Connection: RJ45
- Power/ Data Cable: 26



Download:
signDECO 09/10 Specification 